

Texas Department of License and Regulation

Water Well Driller/Pump Installer Program
 P.O. Box 12157 Austin, Texas 78711 (512)463-7880 FAX (512)463-8616
 Email address: water.well@license.state.tx.us

This form must be completed and filed with the department within 30 days following the plugging of the well.

PLUGGING REPORT

A. WELL IDENTIFICATION AND LOCATION DATA

1) OWNER

| | | | | |
|------|---------|------|-------|-----|
| Name | Address | City | State | Zip |
|------|---------|------|-------|-----|

2) WELL LOCATION

| | | | | |
|--------|------------------|------|-------|-----|
| County | Physical Address | City | State | Zip |
|--------|------------------|------|-------|-----|

| | | | |
|----------------------------|--------------|-------------|---------------|
| 3) Owner's Well No. | Long. | Lat. | Grid # |
|----------------------------|--------------|-------------|---------------|

4) Type of Well Water Monitor Injection De-Watering **5) N-**

Drill, Pump Installer, or Landowner performing the plugging operations **must** locate and identify the location of the well within a specific grid on a full scale gridded map available from Texas Natural Resource Information Service. The location of the well should be denoted within the grid by placing a corresponding dot in the square to the right. The legal description is optional.

B) HISTORICAL DATA ON WELL TO BE PLUGGED (if available)

| | |
|-------------------|-------------|
| 6) Driller | License No. |
|-------------------|-------------|

7) Drilled / / **8) Diameter of hole** _____ Inches **9) Total depth of well** _____ feet.

C. CURRENT PLUGGING DATA

10) Date well plugged / /

12) Name of Driller/Pump Installer or Well Owner performing the plugging

License No.

**13) CASING AND CEMENTING DATA RELATIVE TO THE PLUGGING OPERATIONS.
 CASING LEFT IN WELL**

| DIAMETER (inches) | FROM(feet) | TO (feet) |
|-------------------|------------|-----------|
| | | |
| | | |
| | | |
| | | |

11) REMOVE ALL REMOVEABLE CASING

Please check box beside the method of plugging used

- Tremmie pipe cement from bottom to top.
- Tremmie pipe bentonite from bottom to 2 feet from surface, cement top 2 feet.
- Pour in 3/8 bentonite chips when standing water in well is less than 100 feet depth, cement top 2 feet.
- Large diameter well filled with clay material from top to bottom.

CEMENT/BENTONITE PLUG(S) PLACES IN WELL

COMMENTS

| FROM (feet) | TO (feet) | SACKS |
|-------------|-----------|-------|
| | | |
| | | |
| | | |
| | | |

| |
|--|
| |
| |
| |
| |

D. VALIDATION OF INFORMATION INCLUDED IN FORM

I certify that I plugged this well (or the well was plugged under my supervision) and that all of the statements herein are true and correct. I understand that failure to complete items 1 through 13 will result in the report(s) being returned for completion and resubmitted.

Company or individual's Name (type or print)

| | | | |
|---------|------|-------|-----|
| Address | City | State | Zip |
|---------|------|-------|-----|

| | | | |
|---|-------------|--------------------------------|-------------|
| Signature Licensed Driller/Pump Installer | / / Date | Signature Apprentice | / / Date |
|---|-------------|--------------------------------|-------------|